

# Technical Specifications

## Overview

Dimensions	117 x 45 x 13.3 mm (4.6 x 1.8 x 0.5")
NFC Card & Keyfob Access	Yes
Apple/Google Wallet	Yes
Mobile Unlock	Yes
NDAA Compliant	Yes
Weatherproofing	IP55

## Mechanical

Weight	82 g (2.9 oz)
Enclosure Material	Polycarbonate, aluminum alloy
Mount Material	Stainless steel
Mounting	Wall, gang-box mount (Included) Junction box (Optional)

## Hardware

Indoor and Outdoor Use	Yes
Connectivity	RS-485 BLE 4.1 NFC
Security	OSDP v2
Power Method	DC 12V
Max. Power Consumption	2.5W
Supported Voltage Range	12V DC
ESD/EMP Protection	Air: ±15kV, contact: ±8kV
Speaker	Yes
LEDs	R/G/B/W <a href="#">Learn More</a>
Button	(1) Factory-reset
NFC Frequency	13.56 MHz
NFC Read Range	< 30 mm (1.18")

NFC Technology	ISO 14443A, 14443B, 15693 NFC Tag 1,2,3,4,5 MIFARE Classic MIFARE Plus MIFARE Ultralight MIFARE DESFire
----------------	--

Certifications	CE, FCC, IC
----------------	-------------

Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
-------------------------------	---------------------------------

Ambient Operating Humidity	5 to 90% noncondensing
----------------------------	------------------------

## Software

Management Application	Access
------------------------	--------

Software Information	The software version can be checked at <a href="https://unifi.ui.com">https://unifi.ui.com</a>
----------------------	--