

## Overview

Dimensions	Lock body: 80 x 40 x 35 mm (3.2 x 1.6 x 1.4") Short front plate: 124 x 32 x 3 mm (4.9 x 1.3 x 0.1") Long front plate: 202 x 36 x 3 mm (7.9 x 1.4 x 0.1")
Weight	Lock body: 185 g (6.5 oz) Short front plate: 50 g (1.8 oz) Long front plate: 130 g (4.6 oz)
Enclosure Material	Lock body: zinc alloy Front plate/latches: stainless steel
Lock Features	
Lock Type	Fail secure
Support Door Type	Single door (Wooden/metal)
Holding Force	1,200 kg (2,645 lb)
Current Power	400mA ±10%
Support Voltage Range	12V DC ±10%
Wiring	(1) Lock 12V/NO (red) (1) Lock 12V/COM (black)
Mounting	Door frame recess mount
Door Status Contact	
Type	Dry contact
Logic	Door Open: DPS/+ & DPS/- = Open Door Close: DPS/+ & DPS/- = Short
Rating	Max. 30V DC, 0.1A
Ambient Storage Temperature	-20 to 70° C (-4 to 158° F)
Ambient Operating Temperature	-10 to 60° C (14 to 140° F)
Ambient Operating Humidity	5 to 90% noncondensing

NDAA Compliant

✓

Certifications

FCC, IC, CE